

**Technical Data Sheet** 

Anti-Slip Abrassive Inlay 50mm x 8mm


## PRODUCT DESCRIPTION


Anti - Slip Abrasive Inlay is a composite material with hard wearing silicon carbide anti slip grit, suitable for installation in pre-grooved timber or concrete stairs. The material is suitable for high exposure to salt water and offers high resistance to chemicals such as acid, alkali and solvent liquid.

Material	
Colour	

Composite material with hard wearing silicon carbide anti slip grit.

Black





## Slip Resistance Testing

See Australian Standards Hand Book 198: 2014 (HB 198), "An Introductory Guide to Slip Resistance of Pedestrian Materials" in order to determine a classification of a slip resistance rating. This document outlines the minimum ratings of location and situation of a pedestrian surface.

TEST	AS/NZS 4586:2004 Appendix A
TYPE	Wet Pendulum Test
RATING	Four S slider Mean BPN = 78 Class = P5
TEST	AS/NZS 4586:2004 Appendix D
ТҮРЕ	OIL-WET Ramp
RATING	Mean overall acceptance angle = 35 ° Class R13

## **Luminance Testing**

Compliance for Luminance contrast varies with colour tactile and the substrate onto which you wish to have them installed. Certification of compliance would require testing of the tactile on your surface.